

UPS Technical Specification

Declaration of additional requirements in accordance with IEC 62040-4

DAKER DK Plus		
Subclause IEC 62040-4	Declared environmental aspect	LEGRAND's declared value
5.2.2	Location of manufacturing plant(s)	China
	Environmental management system (certification status and name of system)	ISO 14001
5.2.3	Model	3 101 78
	Power, rated – apparent – active	10000 VA 10000 W
	Representative UPS	No
	Range of UPS covered by representative UPS	-
	UPS configuration	Single UPS with bypass
	Performance classification	VFI-SS-111
	Dimensions (height × width × depth)	440 x 132 x 680 mm
	Mass	26 kg
	Mass of batteries if integrated	-
	Battery technology	-
	Product packaging (mass, material)	Total weight of Reference Product: 31037 g (all packaging included) Packaging as % of weight: - Paper: 13.8% - PS: 1.9% - PE: 0.4%
Group packaging, if applicable (mass, material)	-	
Transportation packaging, if applicable (mass, material)	-	
5.2.4	Substances – Criterion 1	<ul style="list-style-type: none"> - Lead alloyed (CAS 7439-92-1) in the metals and batteries - Lead titanium zirconium oxide (CAS 12626-81-2) in piezoelectric electronic components - Diboron trioxide (CAS 1303-86-2) in some electronic components - Lead not alloyed (CAS 7439-92-1) in some electronic components

UPS Technical Specification

Declaration of additional requirements in accordance with IEC 62040-4

Subclause IEC 62040-4	Declared environmental aspect	LEGRAND's declared value
5.2.5	UPS Efficiency	Up to 94%
	Acoustic Noise	< 50 dBA at 1m
5.2.6	End of life information	<ul style="list-style-type: none">- printed circuit boards if larger than 10 cm²: 14657 g- plastic containing regulated flame retardants- electrolytic capacitors of height > 25 mm and diameter > 25 mm or proportionately similar volume

UPS Technical Specification

Declaration of additional requirements in accordance with IEC 62040-4

DAKER DK Plus		
Subclause IEC 62040-4	Declared environmental aspect	LEGRAND's declared value
5.3.2.2	Recyclable material, (percentage by mass, calculation method) – in product – in packaging	Calculated using the method described in technical report IEC/TR 62635, the recyclability rate of the product is estimated at 74 %. This value is based on data collected from a technological channel operating on an industrial basis. It does not pre-validate the effective use of this channel for the end of life of this product. Separated into: - plastic materials (excluding packaging): 1 % - metal materials (excluding packaging): 35 % - other materials (excluding packaging): 28 % - packaging (all types of materials): 14 %
5.3.2.3	Life cycle assessment	Global warming Total for Life Cycle: 2.96E+04 kgCO2 eq. Raw material and manufacture: 3.71E+02 - 1% Distribution: 1.20E+00 - < 1% Installation: 3.55E-01 - < 1% Use: 2.92E+04 - 99% End of life: 2.49E+00 - < 1% <i>for more details, check the Product Environmental Profile</i>